

Product Information

PC PA-A and B

PRODUCT DESCRIPTION:

PC PA-A and B is a 1:1 by volume two-component, high performance, aliphatic PolyAspartic floor coating. When top coating epoxy floor systems, up to 20 mils thick in a single pass may be achieved, with a working time of 22 minutes at 77 Deg. F at 80% Relative Humidity.

PC PA-A and B provide superior protection through its excellent adhesion, durability, and resistance to oil stains, chemicals, and damaging UV rays for both interior and exterior applications in direct sunlight.

TYPICAL PROPERTIES of the mixed A and B *

PROPERTY	VALUE	UNIT
APPEARANCE:	Clear Light Amber	-
ODOR:	Mild	-
SOLIDS CONTENT:	~92	%
MIXED VISCOSITY @ 25°C (77°F):	200-800	CPS (Brookfield)
COVERAGE of 16 Wet Mils at 25°C (77°F):	95-110	Sq/ft per gallon

*: THE ABOVE INFORMATION IS GIVEN ONLY AS A LISTING OF TYPICAL PROPERTIES AND IS NOT INTENDED TO BE REPRESENTATIVE OF PRODUCT SPECIFICATIONS. PLEASE CONTACT THE QUALITY ASSURANCE DEPARTMENT FOR CURRENT PRODUCT SPECIFICATIONS.

APPLICATIONS OF FLOOR COATINGS FOR:

RESTAURANTS, BARS & CAFETERIAS, SPORTS ARENAS/ STADIUMS, SCHOOLS & UNIVERSITIES, CORRIDORS & LOBBIES, KENNELS, R+D LABS, LOCKER ROOMS / RESTROOMS, GARAGES & AUTO SERVICE AREAS, OFFICES & GENERAL ROOMS, EXTERIOR OR AREAS EXPOSED TO UV, TOPCOAT FOR FLOORS BROADCAST TO REFUSAL OR OTHER FLOOR SYSTEMS

With our proprietary leveling and defoamer package the **PC PA-A and B** minimizes cratering and fisheyes of the cured finish from removing entrained air caused by mechanical mixing and creating a blemish free surface.

SPECIFICATIONS:

Typical product data values should not be used as specifications. Assistance in the preparation of specifications is available by contacting your local Performance Chemicals Representative.

HANDLING AND SAFETY:

MIX BEFORE USE. This material should be stored in tightly sealed containers to prevent free water and particulate contamination from entering the container. Store sealed containers in a dry area at temperatures below 25°C (77°F) or below.

Safety Data Sheets (SDS) are available upon request. Similar information about solvents or other chemicals or materials used with Performance Chemicals' products should be obtained from your suppliers. When solvents and other chemicals are used, proper safety precautions and regulations must be observed.

PC PA-A and B has a very low level of toxicity; however, material is an eye irritant. Take proper precautions to protect the eyes from the silicone fluid by wearing proper safety glasses and face shields. Avoid touching eyes or area around the eye when handling or working with this fluid. Refer to the Additive X-338 SDS for specific information.

Products sold for industrial use only and is not suitable for any device or product inserted inside a human being and may not be suitable for other medical applications.

STORAGE WARRANTY / SHELF-LIFE PERIOD:

The shelf-life period is 12 months from the date of shipment if stored in the original unopened container at 27C/80F or below.

PACKAGING:

PC PA-A and B is available in 5-gallon pails and have a net weight of 44#'s PART A, and 49#'s PART B.

WARRANTY INFORMATION:

The information contained herein is provided in good faith and is believed to be accurate. Because methods of use and conditions of use of our products are beyond our control, this information should not be used in substitution for customer testing to ensure the product is safe and fully satisfactory for the intended use. Performance Chemicals' sole warranty is that the product meets the sales specification in effect at the time of shipment and accepts no liability in negligence or otherwise for any damage resulting from the user reliance on information or recommendations written or verbal. Performance Chemicals specifically disclaims any other express or implied warranty of fitness for a particular purpose or use and disclaims any liability for any incidental or consequential damages. Any suggestions of use shall not be taken as inducements to infringe any patent. 10/27/2025